



1

Doug Smith, MCP/CBO

- ❑ Inspector/Plan Reviewer for over 20 years
- ❑ 19 ICC certifications
- ❑ Certified ICC Master Code Professional and CBO
- ❑ Taught electrical, solar PV, and ESS classes for over 14 years
- ❑ Performed well over ten-thousand electrical, solar PV, and ESS plan reviews
- ❑ Serve on *NEC* CMP 10 representing IAEI
- ❑ Currently serve as a Technical Committee (TC) Member for the following UL standards:
 - UL 61730 (previously 1703) – Flat-Plate PV Modules and Panels
 - UL 1741 - Inverters, Converters, Controllers, and Int. equip...
 - UL 2703 – PV Mounting Systems/Clamps/Gnd. Lugs
 - UL 6703 – Connectors for Use in PV Systems
 - UL 9540 - Energy Storage Systems and Equipment

2

Course Objective/Intent

- ❑ The objective of this presentation is to explain the core *NEC/IFC* requirements that govern commercial solar photovoltaic (PV) systems. This presentation is based on the **2020/2023 *NEC* and 2021 *IBC/IFC***.
- ❑ The intent of this information is to be used as a guide only. This presentation is not intended to indicate any change in any code or local requirements by inference or omission. All diagrams are for illustration purposes only and actual wiring and installation may vary. This presentation is not intended to indicate if one piece or particular brand of equipment is better than another. Also, efficiency and ideal design considerations are not addressed herein. All applicable codes, standards, and manufacturer requirements must always be followed when designing, installing, and inspecting any electrical system, including solar PV and/or battery/energy storage systems.

3


Outline

Commercial (NON-Residential) Solar PV:

1. **PV Modules (solar panels)**
2. **Inverters**
3. **DC Combiners and Re-Combiners**
4. **DC Arc Fault Detection**
5. **Rapid Shutdown**
6. **Grounding and Bonding**
7. **Point of Interconnection Requirements**
8. **AC Combiners**
9. **Available Fault Current for AC Equipment**
10. **Ground-Mounted Installations**
11. **Roof Installations**
12. **2021 *IBC* and *IFC* PV Requirements**
13. **General Equipment Requirements**
14. **Large-Scale Solar PV Systems**
15. **Signage**

Copyright© WC3 2025

4



5

Concept of Series-Connections

□ A circuit with multiple modules that are connected in series is referred to by the *NEC* as a “PV Source Circuit,” but is often called a string of modules by the PV industry (PV string circuit).

(back of a module/solar panel)

Or

Series connected modules

Note: these diagrams are very basic in order to explain the concept of solar panels connected in series. Most modern-day systems are required to also include rapid shutdown components (such components are not shown here).

Copyright© WC3 2025

6

Series vs. Parallel

Series connected modules (solar panels):

Volts from each module add together but **amps** stay the same:

Note: these diagrams are very basic in order to explain the concept of series versus parallel connections. Most modern-day systems are required to also include rapid shutdown components (such components are not shown here).

String (*NEC* refers to this as a “PV Source Circuit”)

Parallel connected modules:

Amps from each module add together but **voltage** stays the same.

Note: solar panels are never connected in this way, this is just an example of parallel connections.

Copyright© WC3 2025

7

Example of how series and parallel connections affect a system

If each module (solar panel) produced 8 amps and 30 volts...

DC Combiner box for parallel connection of multiple strings.

To Inverter

PV output circuit amps= 16 A
PV output circuit volts= 120 V

String amps= 8 A, string volts= 120 V

String amps= 8 A, string volts= 120 V

Note: this is just a basic illustration of how voltage and amperage are affected depending on if the connection is series or parallel. Actual wire and overcurrent sizing must comply with *NEC* 690.8 and 690.9

Note: these diagrams are very basic in order to explain the concept of series versus parallel connections. Most modern-day systems are required to also include rapid shutdown components (such components are not shown here).

Copyright© WC3 2025

8

Jinko® PV Module Specs (example) – Cold Temp dc voltages

Module Type	JKM3205M-60-V	JKM3205M-60-V	JKM3205M-60-V
	STC	NOCT	NOCT
Maximum Power (Pmax)	295Wp	216Wp	220Wp
Maximum Power Voltage (Vmp)	32.2V	30.2V	30.4V
Maximum Power Current (Imp)	9.02A	7.15A	7.24A
Open Circuit Voltage (Voc)	37.5V	36.7V	36.8V
Short-circuit Current (Isc)	9.55A	7.81A	7.88A
Module Efficiency (STC, %)	17.72%	18.02%	18.25%
Operating Temperature (°C)	-40°C~+85°C		
Maximum System Voltage	1000VDC-DL and EC		
Maximum Series Fuse Rating	20A		
Power Tolerance	0~+3%		
Temperature Coefficient of Pmax	-0.39%/°C		
Temperature Coefficient of Voc	-0.29%/°C		
Temperature Coefficient of Isc	0.048%/°C		
Nominal Operating Cell Temperature (NOCT)	45±2°C		

9

Cold Temperature DC Voltage

Example

Maximum dc voltage of a solar PV system on a NON-residential building cannot exceed **1,000V (NEC 690.7)**

Maximum system DC voltage calculation:

Open Circuit Voltage (Voc) of modules= 39.5V DC (at 25°C or 77°F)

39.5V x 21 modules on a dc string = **829.5V** (at 77°F)

If we use -28°C for our coldest temperature (which is noted in the ASHRAE Fundamentals Handbook for Bozeman, MT):

The difference in temperature drop from 25°C to -28°C is **53°C**.

Per the module's specs, the voltage of the modules increases by .29% for every 1°C drop in temperature.

Take 53°C x .29 = a voltage increase of 15.37% at -28°C.

829.5V x 1.1537 = a cold temperature voltage of **957V**.

Copyright© WC3 2025

10

Cold Temp dc Voltages (continued)

NEC 690.7:

- ❑ If solar module temperature coefficients are not available, *NEC* Table 690.7 can be used to determine dc voltages based on cold outdoor temperatures. But doing so will result in higher calculated voltages.
- ❑ OR for PV systems 100kW or greater, an engineered design using industry standard methods, can be used for calculating the maximum dc voltages of a system.
 - An example of an industry standard method could be a *Photovoltaic Array Performance Model*, per Sandia National Laboratories software.

11

Inverters

Copyright© WC3 2025

12

Utility Interactive Inverters

- Any PV Inverters (commercial or residential) that are interconnected with the electric utility grid must meet UL 1741 and be listed as "utility interactive" having anti-islanding protection, NEC 705.40.



Copyright© WC3 2025

13

Inverters

- For commercial use, inverter's AC output voltage can be 208V, 240V, 277V, or 480V for 1-phase or 3-phase systems (depending on the model).



SMA® Tripower Core™ String Inverter



SolarEdge® SE66.6kUS String Inverter



CPS® 60kW String Inverter

Copyright© WC3 2025

14

String Inverters

String inverters will have one or more dc strings connect to the inverter. Sometimes string inverters also include a dc combiner.



Copyright© WC3 2025



15

Central Inverters



Large inverters, often called "central inverters," will typically include what are often referred to as re-combiners.

Re-combiners combine more than one dc output of other dc combiners.



Copyright© WC3 2025

16

Micro inverters

Micro inverters are installed directly underneath the solar panels and convert dc power to ac power right at the solar panel.



Enphase® IQ8+™
Micro inverter



AP Systems® YC600
Micro inverter

Copyright© WC3 2025


17


DC Combiners and Re-Combiners

Copyright© WC3 2025

18

DC Combiner Box






Copyright© WC3 2025

19

OCPDs For Each Positive And Negative Conductors is no longer required [See *NEC 690.9(C)*]




MidNite Solar Combiner Boxes

Copyright© WC3 2025

20

Some string inverters have dc combiners, and others do not



The above shown string inverters DO have a dc combiner built-in as part of the inverter.

Copyright© WC3 2025

21

Some string inverters have dc combiners, and others do not (continued)



The above shown string inverter does NOT have a dc combiner built-in as part of the inverter.

Copyright© WC3 2025

22

NEC – 690.4(B)

Listing of equipment:

- ❑ DC combiners are included at the list of equipment that are required to be listed for the PV application.



ETL
 MAX. SYSTEM OUTPUT: 250A
 MAX. INPUT PER POLE: 17A
 CONFORMS TO UL STD. 1741

Copyright© WC3 2025

23

Re-Combiners



Positive conductors from combiner boxes each terminate to their own fuse at the re-combiner located within the inverter.



Re-combiner within a central inverter

Copyright© WC3 2025

24

Re-Combiner (another example)

Positive conductors from combiner boxes each terminate to their own fuse at the re-combiner located within the inverter.

Re-combiner within a central inverter

Note: sometimes dc strings are combined together using a cable harness system. See the large-scale PV systems portion of this presentation for more info.

Copyright© WC3 2025

25

How to size dc wiring for the "PV output circuit" of a dc combiner

Service equipment

Sub-panel feeder circuit (existing)

Sub-panelboard

Inverter AC output circuit terminates at a 3 pole breaker at sub-panel

AC disconnect

Inverter (with a transformer)

DC disconnect and PV output combiner box

NOTE: grounding and bonding is not shown on this diagram but is **required** for all solar PV and electrical systems.

Copyright© WC3 2025

26

Jinko® PV Module Specs (example) – Conductor (wire) Sizing

SPECIFICATIONS			
Module Type	JK60M040-V	JK60M040-V	
Maximum Power (Pmax)	295Wp	295Wp	295Wp
Maximum Power Voltage (Vmp)	32.2V	32.2V	32.4V
Maximum Power Current (Imp)	9.02A	7.15A	9.10A
Open-circuit Voltage (Voc)	39.6V	38.6V	39.7V
Short-circuit Current (Isc)	9.55A	9.1A	9.61A
Module Efficiency (STC %)	17.72%		18.02%
Operating Temperature (TC)	-40°C ~ +85°C		
Maximum System Voltage	1000VDC (UL and IEC)		
Maximum Series Fuse Rating	20A		
Power Tolerance	0 ~ +3%		
Temperature Coefficients of Pmax	-0.39%/°C		
Temperature Coefficients of Voc	-0.29%/°C		
Temperature Coefficients of Isc	0.048%/°C		
Nominal Operating Cell Temperature (NOCT)	45°C		

WARRANTY: LINEAR PERFORMANCE WARRANTY 30 Year Product Warranty

TESTING: IEC 61215, IEC 61730, ISO 9001, ISO 14001, ISO 45001

27

Example – Conductor And OCPD Sizing

1. Max current
NEC 690.8(A)(1)(a)

2. Breaker or fuse size
NEC 690.8(B) & 690.9(B)


	1. Max current <i>NEC 690.8(A)(1)(a)</i>	2. Breaker or fuse size <i>NEC 690.8(B) & 690.9(B)</i>
String circuit (Source Circuit)	(string Isc x 125%) 9.55 x 1.25 = 11.9 A	(string max current x 125% again) 11.9 x 1.25 = 14.9 A
PV output Circuit (circuit between combiner box and inverter)	(all combined strings max current from above line) 11.9 x #of strings = 119 A	(Total combined strings max current x 125%) 119 x 1.25 = 148.8 A
Inverter AC Output Circuit	(inverter max output) _____ amps	(inverter max output x 125%) _____ x 1.25 = _____ A

Use the max amps in this column when starting the adjustment of wires for temp. and conduit fill. Take the larger of either the final adjusted ampacity from this column or the final amps in column 2 to size the conductors, NEC 690.8(B)(2).

If no deration or adjustment of wires is needed then use this column to size wires. Use this column to size the breaker or fuses (use next size up breaker or fuse if between ratings).

Copyright© WC3 2025

28



29

DC Conductor and OCPD Sizing (continued)

	1. Max current <small>NEC 690.8(A)(1)(a)</small>	2. Breaker or fuse size <small>NEC 690.8(B) & 690.9(B)</small>
String circuit (Source Circuit)	(string Isc x 125%) 9.55 x 1.25= 11.9 A	(string max current x 125% again) 11.9 x 1.25= 14.9 A
PV output Circuit (circuit between combiner box and inverter)	(all combined strings max current from above line) 11.9 x #of strings= 119 A	(Total combined strings max current x 125%) 119 x 1.25= 148.8 A
Inverter AC Output Circuit	(inverter max output) ___amps	(inverter max output x 125%) x 1.25= ___ A

Per **NEC 690.8(B)(1)** exception, and **690.9(B)(2)**, the second 125% factor does not need to be applied when the conductors connect to an assembly together (with its overcurrent protection devices) is listed for continuous operation at 100% of its rating.

Copyright© WC3 2025

30

❑ In this example, the switchboard label is indicating that the continuous loads cannot exceed 80% of the rating of the OCPD, therefore the exception of **690.9(B)(1) cannot be used.**

CATALOG NUMBER: BES34X240315-1
 MANUFACTURING DATE: 8/2024
 ORDER NUMBER: SO31624-1390P
 SECTION: 1 OF 2
 SWITCHBOARD #: SWBD-D001
 SECTION #: D001-1
 VOLTAGE: 480/277
 PHASE: 3
 WIRE: 4
 HZ: 60
 SSCR: 65KAIC @ 480VAC
 MAIN AMPS MAXIMUM: 2000
 NEUTRAL AMPS MAXIMUM: 2000

DEVICES TO BE INSTALLED OR REPLACEMENT UNITS SHALL BE FROM THE SAME MANUFACTURER, OF THE SAME TYPE AND HAVE EQUAL OR GREATER INTERRUPTING CAPACITY.

MAXIMUM CONTINUOUS LOADS NOT TO EXCEED 80% OF THE OVERCURRENT PROTECTIVE DEVICE (CIRCUIT BREAKER AND FUSES) RATINGS EMPLOYED IN OTHER THAN MOTOR CIRCUITS. EXCEPT FOR THOSE CIRCUITS EMPLOYING CIRCUIT BREAKERS MARKED AS SUITABLE FOR CONTINUOUS OPERATION AT 100% OF THEIR RATINGS.

Copyright© WC3 2025

31

Option for Simulated Maximum Current of the System

NEC 690.8(A)(1)(a)(2):

- ❑ For **PV systems 100kW or greater**, an engineered design using industry standard simulated methods, can be used for calculating the maximum dc **current** of a system **instead of** increasing the short circuit rating of the modules by 125%.
 - An example of an industry standard method could be a *Photovoltaic Array Performance Model*, per Sandia National Laboratories software.

The 3-hour maximum simulated current cannot be less than 70% of the short circuit current (Isc) multiplied by 125%.

	1. Max current <small>NEC 690.8(A)(1)(a)</small>	2. Breaker or fuse size <small>NEC 690.8(B) & 690.9(B)</small>
String circuit (Source Circuit)	(string Isc x 125%) 9.55 x 1.25= 11.9 A	(string max current x 125% again) 11.9 x 1.25= 14.9 A
PV output Circuit (circuit between combiner box and inverter)	(all combined strings max current from above line) 11.9 x #of strings= 119 A	(Total combined strings max current x 125%) 119 x 1.25= 148.8 A
Inverter AC Output Circuit	(inverter max output) ___amps	(inverter max output x 125%) x 1.25= ___ A

Copyright© WC3 2025

32

DC Arc-Fault Detection

Copyright© WC3 2025

33

Arc-Fault Protection (AFPD)

- ❑ Section **690.11** of the **NEC** requires that a PV system with DC circuits that operate at 80 volts or greater, shall be protected by a listed PV DC arc-fault circuit interrupter or have listed system components that provide equivalent protection.
- ❑ This section does not apply to micro inverter or ac module systems that are currently on the market.

34

NEC 690.11 – DC Arc-Fault Protection

Exceptions:

- ❑ DC conductors that are part of MC cable, in metal raceways, enclosed metal cable trays, or buried underground do not require DC arc-fault protection as long as the circuit conductors are also installed per one of the following:
 - NOT installed on or in a building
 - Or are located in or on a detached building that is dedicated for the PV system equipment.



35

Arc-Fault Protection Continued...



36

Arc-Fault Protection Continued...



37

Arc-Fault Protection Continued...



38

Rapid Shutdown

Copyright© WC3

39

Rapid Shutdown

690.12(B) Controlled Limits:

- The use of the term **array boundary** in this section is defined as **(1 ft) from the array in all directions (and 3' into the attic)**. Controlled conductors outside the array boundary shall comply with *NEC* 690.12(B)(1) and inside the array boundary shall comply with 690.12(B)(2).



Copyright© WC3 2025

40

Rapid Shutdown

❑ **(B)(1) Outside the Array Boundary.** For any controlled conductors that are located outside the boundary are limited to not more than **30 volts within 30 seconds** of rapid shutdown initiation.

Copyright© WC3 2025

41

Rapid Shutdown

690.12(B)(2) Inside the Array Boundary:

❑ The PV system is required to comply with *one* of the following:

- (1) The system be listed as a “PV hazard control system” (PVHCS per **UL 3741**) installed per manufacturer’s instructions and listing of the system, shall be installed in accordance with the instructions included with the listing or field labeling of the system. Also, when the system requires initiation to a controlled state, the rapid shutdown initiation device required in 690.12(C) is required for the initiation.
- (2) The system be provided with “shock hazard control” for firefighters to reduce the voltage of the system’s controlled conductors to not more than **80 volts within 30 seconds** of rapid shutdown initiation.

Copyright© WC3 2025

42

UL 3741

There are currently on the market PV systems available which are listed UL 3741 as a PV Hazard Control System. Such systems often require the inverter to be installed within 1 foot of the solar array.

ALWAYS follow the manufacturer’s installation instructions!!

Copyright© WC3 2025

43

UL 3741 continued...

UL 3741 listed systems installed per the manufacturer’s instructions, and per the listing of the equipment, are considered as meeting the rapid shutdown requirements of 690.12.

Copyright© WC3 2025

44

Carpports/Shade Structures



Per the 2023 NEC, Section 690.12, non-enclosed detached structures do **NOT** require rapid shutdown functionality.

Copyright© WC3 2025

Rapid Shutdown Initiation Device

NEC 690.12(C) Initiation Device:

- ❑ For **NON** one-family and two-family dwellings, the initiation device is **NOT REQUIRED** to be at a readily accessible location on the outside of the building.
- ❑ The rapid shutdown initiation device(s) shall consist of at least one of the following:
 - (1) Service disconnecting means.
 - (2) PV system disconnecting means.
 - (3) Readily accessible switch that plainly indicates whether it is in the "off" or "on" position.

There are not allowed more than six switches or six sets of circuits breakers (or a combination of breakers with switches) for multiple PV systems that are installed with rapid shutdown functions on a single service.

Rapid Shutdown Initiation Device



The type of rapid shutdown initiation device used will depend on the type of rapid shutdown components of the system.

Copyright© WC3 2025

Rapid Shutdown Signage

- ❑ **690.12(D) [previously 690.56(C)] Buildings with Rapid Shutdown.** Buildings with PV systems shall have permanent labels as described in 690.12(D)



Copyright© WC3 2025

Rapid Shutdown Signage

2020 NEC Info Note Figure 690.56(C), and 2023 NEC Info Note Figure 690.12(D)

SOLAR PV SYSTEM EQUIPPED WITH RAPID SHUTDOWN

TURN RAPID SHUTDOWN SWITCH TO THE "OFF" POSITION, TO SHUTDOWN CONDUCTORS OUTSIDE THE ARRAY. CONDUCTORS WITHIN ARRAY REMAIN ENERGIZED IN SUNLIGHT

SOLAR PV SYSTEM EQUIPPED WITH RAPID SHUTDOWN

TURN RAPID SHUTDOWN SWITCH TO THE "OFF" POSITION TO SHUTDOWN PV SYSTEM AND REDUCE SHOCK HAZARD IN ARRAY

(note: this sign was removed from the 2020 NEC)

See also 1205.4 in the 2021 IFC for similar requirements.

49

Rapid Shutdown Signage For Buildings with More Than One Rapid Shutdown Type

NEC 690.12(D)(1) [previously 690.56(C)(1)] Buildings with More Than One Rapid Shutdown Type:

- ❑ When a building has multiple PV systems with more than one type of rapid shutdown, **or** a PV system with a rapid shutdown type and a PV system with no rapid shutdown, then a detailed diagram of the roof shall be provided to show each separate PV system, and the diagram must include a dotted line around areas that remain energized after rapid shutdown is initiated.

50

Rapid Shutdown Signage For Buildings with More Than One Rapid Shutdown Type

Example of a plaque showing which portion(s) of the PV system are equipped with rapid shutdown and which are not:

Copyright© WC3 2025

51

Rapid Shutdown Switch Signage


- ❑ **NEC 690.12(D)(2) [previously 690.56(C)(2)] Rapid Shutdown Switch.** There must be provided a sign on or within 3 feet of the rapid shutdown switch and such sign must include the following wording: **“RAPID SHUTDOWN SWITCH FOR SOLAR PV SYSTEM”**
- ❑ The label is required to have all letters be capitalized having a minimum height of 3/8 inches with white words on red background.

Rapid Shutdown Switch For Solar PV System


Sign located next to the rapid shutdown disconnect

Copyright© WC3 2025


52




53



54




55




56

Bonding to Support Rails



WEEBL 6.7 assembly
(Wiley Electric/Burndy)


WEEBL Grounding Lug



Metal parts of the PV system are required to be bonded to the equipment grounding conductor. NEC 690.43.

Copyright© WC3 2025

57



WEEBL lay-in lug assembly

Copyright© WC3 2025

58


Violations!!!



Copyright© WC3 2025

59

Bonding of Support Rails




Missing stainless steel washer between rail and lay-in lug.

Stainless steel washer installed when connecting lay-in lug to galvanized metal surfaces.

OK

Copyright© WC3 2025

60



Grounding lugs outdoors must be outdoor rated! Typically, they will be listed for direct burial. This one does not have DB marking on it.

Copyright© WC3 2025

61


Ground-Mounted System Racking With Integrated Bonding



Copyright© WC3 2025

62


Bonding at Array



Devices or equipment that bond solar modules (panels) together must be listed for the application. *NEC 690.43(A)*.

Copyright© WC3 2025

63



Devices used for bonding solar modules together or to support rails must be listed and tested for the application. *NEC 690.43(A)*.

Copyright© WC3 2025

64

Bonding at Conduit




Verify that any bond bushings and ground lugs used outdoors are listed for wet locations (they will often also be listed for direct burial). NEC 110.3(B).

Violation?

Copyright© WC3 2025

65

Installation Errors




Is the conduit bonded to an equipment grounding conductor?

Wire fill issues?

No bushing at end of conduit

Copyright© WC3 2025




An equipment grounding conductor has not been extended from the array to the inverter. Major VIOLATION!

66

Required Equipment Grounding Conductor Must Extend to Inverter

The equipment grounding conductor(s) which connect to racking and solar modules (and other metal parts) must extend to the inverter served!



Must bond these sections of array to each other

Copyright© WC3 2025

67



Copyright© WC3 2025

68


Grounding and Bonding

2020 NEC 690.47(A) - Grounding Electrode System:

- ❑ A building or structure that supports a PV system must have a grounding electrode system (per Part III of NEC Article 250).
- ❑ For connection of the PV system to the grounding electrode system, either of the applicable following methods must be used:
 - PV systems that are NOT solidly grounded (such as functionally grounded systems) the equipment grounding conductor (EGC) of inverter's ac output circuit is permitted to be the only connection to ground for the PV system when such equipment ground wire is connected to a distribution system that is already connected to a grounding electrode system.
 - The second option applies to solidly grounded PV systems [see 690.41(A)(5)]. These systems are very rare.


69

Enphase® IQ7+™ Micro Inverter System




70

Same wire used as both the EGC and grounding electrode conductor for the inverter - 690.47(A)(1)




71


Example System - Grounding




72




73



74



75



76

Splices and Taps

230.46 – Splices and Taps

- Any pressure connectors and devices for splicing or taps onto service conductors must be marked "suitable for use on the line side of the service equipment," or equivalent wording. Per UL, the use of 'SR' or 'SVC' is also allowed.



Copyright© WC3 2025

77


Multiple Sources of Power

705.10 – Identification of Power Sources:

- A permanent plaque, label, or directory is required to be installed at each service equipment location (or other approved readily visible location). Such must denote the location of each power source disconnecting means for the building or structure and be grouped with any other plaques or directories.
- New for 2023 NEC, the plaque, label, or directory must also include the emergency phone number of any off-site companies/entities that service the power source system(s).
- Such plaque, label, or directory must be marked with the words "CAUTION: MULTIPLE SOURCES OF POWER."

78


Supply (line) Connections Vs Load Connections



Copyright© WC3 2025

79


Supply (line) side connection – Made Outside of a Building



Copyright© WC3 2025

80

Modifications of Equipment?




Cannot drill or modify electrical equipment unless permitted per the manufacturer's instructions, or the modification must be field evaluated for the application (and be field labeled). NEC 110.3(B) and 705.11(D) [2020 NEC].

Copyright© WC3 2025

81

Supply (line) side connection – Made **Inside** of a Building



Supply-side taps (point of connection) made inside the building

480V Service Equipment

1,000A Main

Existing load breaker

Existing load breaker

Pass-through breaker or fused disconnect [must be listed as service equipment, per NEC 705.11 and 230.82(6)]

600A

To electric utility

Max length of 10 feet

Inverter

AC out

Inverter AC Output circuit (neutrals and grounding conductors not shown)


Grounded conductors and grounding conductors (EGCs & GECs) not shown on this slide

(Inside of a building)

Copyright© WC3 2025

82

Supply (line) side connection (2020 NEC) – Made **Inside** of a Building



Supply-side taps (point of connection) made inside the building

480V Service Equipment

1,000A Main

Existing load breaker

Existing load breaker

Pass-through breaker or fused disconnect [must be listed as service equipment, per NEC 705.11 and 230.82(6)]

600A

To electric utility

Max length of 71 feet

Inverter

AC out

Inverter AC Output circuit (neutrals and grounding conductors not shown)

Grounded conductors and grounding conductors (EGCs & GECs) not shown on this slide

Cable limiters


Note: this method is no longer allowed per the 2023 NEC!

For non-dwellings, the overcurrent protection device can be located within **71 feet** (maximum conductor length) as long as cable limiters are provided for each ungrounded conductor. The cable limiters would need to be within **16.5 feet** of the point of connection (maximum conductor length).

Copyright© WC3 2025

83

Supply (line) side connection continued...




Examples of cable limiters


Cooper Bussman cable limiter

Ferraz Shawmut cable limiters


84



85



86




87

Load Side Connections – 705.12

- ❑ Load side connections occur after (downstream of) the main electrical service disconnect(s).
- ❑ The requirements of NEC 705.12 in the 2023 NEC are similar to those shown in 705.12 of the 2020 NEC, with a few minor changes.
- ❑ **For the purposes of this presentation, the NEC sections referenced on the following slides are per 2020 NEC unless otherwise noted on the slide.**

88

Load-Side Interconnection Example



89

705.12(B) - Bus or Conductor Ampacity Rating

Bus or Conductor Calculations:

- ❑ 125% of the inverter(s) AC (or “power source”) output current is to be used when determining the ampacity calculations of 705.12(B)(1) through (B)(3).

Technical data	Sunny Tripower CORE1 (US)
Input (DC)	
Max. array power	75000 Wp STC
DC voltage (max)	1000 V
Rated MPPT voltage range	500 V...800 V
MPPT operating voltage range	150 V...1000 V
Min. DC voltage / start voltage	150 V / 188 V
Number of independent MPPT trackers / strings per MPPT input	4 / 2
Max. operating input current / per MPPT tracker	120 A / 20 A
Max. short circuit current per MPPT / string input	30 A / 30 A
Output (AC)	
AC nominal power	50000 W
Max. AC apparent power	53000 VA
Output phases / line connections	3 / 3 (N) PE
Nominal AC voltage	480 V / 277 V WYE
AC voltage range	244 V...305 V
Rated AC grid frequency	60 Hz
AC grid frequency / range	50 Hz, 60 Hz / 49...+5Hz
Max. output current	64 A
Power factor (power / adjustable displacement)	1 / 0.0 leading...0.0 lagging
Harmonics THD	<3%

Example:
64 amps × 1.25 = 80 amps



SMA® CORE1 Inverter specs

90

705.12(B)(1) – Feeders

Feeders

- ❑ When an inverter (“power source”) connection is made to a feeder, the feeder is required to have an ampacity not less than 125% of the output current (amps) of the inverter(s).
- ❑ Per 705.12(B)(1), when the inverter (“power source”) AC output connection is made to a feeder at a location **other than** the opposite end of the feeder from the primary source overcurrent device, the portion of feeder on the load side of the inverter (“power source”) output connection must be protected by **NEC 705.12(B)(1)(a)** or (B)(1)(b).

Copyright© WC3 2025

91

705.12(B)(1) (Feeders) continued...


- ❑ If the PV connection to a feeder is **not** at the opposite end of the feeder from the feeder’s main breaker (primary overcurrent protection device), the feeder’s ampacity on the load side of the PV connection must be as per **NEC 705.12(B)(1)(a)** or (B)(1)(b):
 - The feeder ampacity must not be less than the sum of the primary source OCPD and 125% of the inverter(s) (power source) output current.

OR


 - An overcurrent device on the **load side** of the inverter (power source) AC output connection must be rated not greater than the ampacity of the feeder.

Copyright© WC3 2025

92



93



94

NEC 705.12(A)(3) [2023 NEC] – Taps

Feeder Taps:

- ❑ Where inverter (power source) AC output circuits tap feeder conductors, the **taps** are to be sized based on 125% of the inverter (power source) output circuit current.
- ❑ If either NEC 240.21(B)(2) or (B)(4) will be used (for taps OVER 10 feet and up to 25 feet long), then the ampacity of the taps cannot be less than 1/3 of the sum of the rating of the OCPD that is protecting the feeder conductors plus the rating of the power source OCPD.

95

NEC 705.12(A)(3) – Taps continued...

Neutral conductors and grounding conductors (EGCs & GECs) not shown on this slide


Copyright© WC3 2025

96

NEC 705.12(B)(3) – Busbars

Busbars


- NEC 705.12(B)(3)(1) through (B)(3)(6) must be used for determining the minimum ratings of busbars, unless the distribution equipment has specific listing and instructions for combining multiple sources.



Copyright© WC3 2025

97

Busbars – Example For Method “1” [NEC 705.12(B)(3)(1)]



Neutral conductors and grounding conductors (EGCs & GECs) not shown on this slide

400A + 80A = 480A
The sub-panel’s busbar rating is exceeded! Violation!

Copyright© WC3 2025

98

Method “2” [NEC 705.12(B)(3)(2)]


2) Where two sources, one a utility (primary power source) and the other an inverter (or other power source), are located at opposite ends of a busbar that also has other loads, the sum of the rating of the OCPD protecting the busbar and the inverter(s) (power source) current rating x 125% cannot exceed 120% of the rating of the busbar.

- The busbars must already be sized for the connected loads as per Article 220 in the NEC.
- A sign must be provided next to the backfed PV breaker stating: “WARNING: POWER SOURCE OUTPUT - DO NOT RELOCATE THIS OVERCURRENT DEVICE”

Copyright© WC3 2025

99

Example for method “2” [NEC 705.12(B)(3)(2)]




Neutral conductors and grounding conductors (EGCs & GECs) not shown on this slide

400A + 80A = 480A
400A rated sub-panel x 120% = up to 480 amps allowed

Copyright© WC3 2025

100



101

Method "3" [*NEC 705.12(B)(3)(3)*]

3) The sum of the ampere ratings of all breakers (OCPDs) on panelboards, including load and supply breakers (but NOT counting the main breaker protecting the panel), must not exceed the rating of the panelboard's busbars.

- The rating of the main breaker protecting the panelboard must not exceed the rating of the busbars.
- Permanent warning label must be applied to the panel (distribution equipment) with the words: "WARNING: EQUIPMENT FED BY MULTIPLE SOURCES. TOTAL RATINGS OF ALL OVERCURRENT DEVICES, EXCLUDING MAIN SUPPLY OVERCURRENT DEVICE, SHALL NOT EXCEED THE AMPACITY OF BUSBAR."

102

Example for method "3" [*NEC 705.12(B)(3)(3)*]

For option #3, The combined ratings of all breakers shown in this panelboard must not exceed the rating of the panelboard's busbars.

The main breaker is **NOT** counted when adding up the breakers.

WARNING: THIS EQUIPMENT IS FED BY MULTIPLE SOURCES. TOTAL RATINGS OF ALL OVERCURRENT DEVICES, EXCLUDING MAIN SUPPLY OVERCURRENT DEVICE, SHALL NOT EXCEED THE AMPACITY OF THE BUSBAR

Required Sign

400A rated panel

Copyright© WC3 2025


103

Method "5" [*NEC 705.12(B)(3)(5)*]

6) Connections made to switchgear, switchboards, and panelboards that are in configurations differing from *NEC 705.12(B)(3)(1)* through (B)(3)(4) are permitted as long as designed under engineering supervision that includes available fault-current and busbar load calculations.

Copyright© WC3 2025


104



105



106



107



108

Back-fed Equipment

Neutral conductors and grounding conductors (EGCs & GECs) not shown on this slide

A PV system effects all equipment and conductors that are backed by the PV system all the way back to the service equipment. NEC 705.12(B) applies to all equipment and conductors being backed on the load side of main service disconnect.

480V service equipment rated 600A
 600A Main
 Existing load breaker
 Existing load breaker
 175A
 480V/208V Transformer
 400A rated 208V panelboard
 200A rated 208V panelboard
 200A tie-in breaker
 80A
 From a 208V Inverter
 To electric utility
 ← 34.6A of PV on 480V side of transformer

Note: To determine what 80A on the 208V side of above transformer looks like on the 480V side of the transformer, simply take the 208V and divide by 480V = ratio of .433 x 80A = 34.6A

Copyright© WC3 2025

109

Example System #1 – Point Of Interconnection

Neutral conductors and grounding conductors (EGCs & GECs) not shown on this slide

480V Service Equipment
 600A Main
 Existing load breaker
 Existing load breaker
 400A
 To electric utility
 Sub-panel rated 400 amps
 100A
 Inverter AC Output circuit (neutrals and grounding conductors not shown)

The sum of the breaker feeding the sub-panel plus the solar PV (400A main breaker plus the 100A solar) cannot exceed 120% of the rating of the sub-panel.

400 amp rated panel x 1.2= 480amps

Only a 80A PV backed breaker can be added to the sub-panel at end of bus bars.

Copyright© WC3 2025

110

Example System #1 – Point Of Interconnection Continued...

Neutral conductors and grounding conductors (EGCs & GECs) not shown on this slide

480V Service Equipment
 600A Main
 Existing load breaker
 Existing load breaker
 350A
 To electric utility
 Sub-panel rated 400 amps
 100A
 Inverter AC Output circuit (neutrals and grounding conductors not shown)

If the main breaker for the sub-panel is reduced to 350 amps:
 $350A + 100A = 450A < 480A$

Ok to add new 100 amp PV backed breaker ONLY if new 350A breaker feeding the panel is sized for all loads connected to the sub-panel per NEC 220.

Copyright© WC3 2025

111

Example System #1 – Back-Fed Service Equipment

Neutral conductors and grounding conductors (EGCs & GECs) not shown on this slide

480V Service Equipment
 600A Main
 Existing load breaker
 Existing load breaker
 350A
 To electric utility
 600A rated busbars
 OK
 Sub-panel rated 400 amps
 100A
 Inverter AC Output circuit (neutrals and grounding conductors not shown)


The sum of the main breaker plus the solar feeding the service equipment bus bars cannot exceed 120% of the rating of the bus bars if backed fed breaker is located at end of bus bars.

600 amp rated bus bars x 1.2 = 720amps


600A main + 100A PV breaker = 700A feed the bus bars. $700A < 720A$.

Copyright© WC3 2025


112




113



114



115



116

Photo of a Switchboard



Copyright© WC3 2025

117

Panelboard (example)



Copyright© WC3 2025

118

AC Combiner Panel (if needed)

Copyright© WC3 2025

119


AC Combiner Panels




- Panelboards (or switchboards) which are dedicated for the connection of PV inverter breakers do not need to follow the requirements of NEC 705.12(B) as long as there are no loads in such panelboard/switchboards.

Copyright© WC3 2025


120



121



122




123


Available Fault Current (for AC equipment)

Copyright© WC3 2025


124




125



126



127



128

Example Fault Current Calculation (continued)

TRANSFORMER - T2	
KVA	45
Voltage	208
%Z	2.00
%Z TOL	No Change
FAULT - X5	
Available Fault Current	5,017 AMPS
Voltage (L-L)	208 V

Fault current at the secondary side of the 45KVA transformer

CONDUCTOR RUN - C4	
LENGTH	10 FT
SIZE	3
QTY (per phase)	1
TYPE	Three Single Conductors
CONDUIT	Steel
WIRE	Cu, 600 V
FAULT - X6	
Available Fault Current	5,033 AMPS
Voltage (L-L)	208 V


Fault current at AC combiner panel

*Calculation using the free Cooperbusman fault current calculator

129

Available Fault Current (See example calculation handout)

All AC equipment must have a fault current rating not less than the calculated available fault current that could be provided to the equipment!



Copyright© WC3 2025

130

Ground-Mount Installations

Ground-Mount Installations

Copyright© WC3 2025

131

Wire Protection (where DC conductors are readily accessible)

NEC 690.31(A):

- Where PV source and output circuits operating at voltages greater than 30 volts are installed in readily accessible locations, circuit conductors shall be **guarded or installed in Type MC cable or in raceway.**



"Guarded circuit conductors?"

Copyright© WC3 2025

132




133



134



135



136

Roof Installations

Copyright© WC3 2025

137

PV Modules On Commercial Roofs



Copyright© WC3 2025

138

Ballasted Roof Mounted Systems



Ballasted systems typically are only allowed to have a tilt of 0 to 25°



Photo courtesy of Unirac Incorporated

Copyright© WC3 2025

139

Ballasted Roof Mounted Systems

- ❑ Engineering should be obtained to justify that the existing roof can handle the weight of the PV system with ballast blocks installed.
- ❑ A detailed layout must also be obtained from the racking manufacturer to show the exact layout of the array, show how many ballast blocks are required per racking tray, and to show that the system can handle local wind and seismic loads.




Copyright© WC3 2025

140

In order to reduce weight of a ballasted system, some systems utilize roof anchors periodically throughout the array.

The roof anchor system must be installed per the racking manufacturer's requirements.



Copyright© WC3 2025

141

Structural Integrity

Copyright© WC3 2024



Make sure the roof structure is adequate to support the PV system. This is especially important for ballasted PV racking systems.

142

Roof Flashings Required



Properly flashed supports

Copyright© WC3 2025

143

Wire Management



Copyright© WC3 2025


144

Wire Management



145

Wire Management



146

Wire Management




147


Wire Management




148




149



150



151



152

Equipment Mounted to Parapets



Copyright© WC3 2025

153

Junction Boxes



Copyright© WC3 2025

154

2021 IBC and IFC PV Requirements

2021 IBC and IFC PV Requirements

Copyright© WC3 2025

155

2021 International Building Code (IBC) Requirements

- ❑ PV modules installed on the roof must be labeled to identify their fire classification, IBC 1505.9.
- ❑ The listed fire class must meet IBC table 1505.1 based on the type of construction of the building, IBC 1505.9.



Copyright© WC3 2025

156

2021 IBC Requirements Continued...

- ❑ **IBC 1507.16.6:** PV shingles or Building Integrated PV (BIPV) must be listed per UL 7103, or both UL 61730-1 and UL 61730-2.



Copyright© WC3 2025

157

Building Integrated PV (BIPV)



(Photo courtesy of Canadian Solar)




Uni-Solar (United Solar) modules on Coke bid.

158

2021 IFC Required Pathways On Non-Residential Roofs (1205.3.1-1205.3.3)

(If either axis of the roof is 250 ft. or less)




Roof access, skylights, ventilation hatches, or standpipes.

No section of an array can exceed 150' x 150'

Copyright© WC3 2025

159

2021 IFC Required Pathways On Non-Residential Roofs (1205.3.1-1205.3.3)




Roof access, skylights, ventilation hatches, or standpipes.

No section of an array can exceed 150' x 150'

Copyright© WC3 2025

160




161



162




163



164

Violations!




Clear working space is required per NEC 110.26.

LOTS of violations!!

Copyright© WC3 2025

165

Disconnects From All Sources



NEC 690.15(C) requires disconnects for inverters from all sources of power.

The required disconnect(s) must be within sight and within 10' of the equipment unless the disconnecting means is lockable or located behind a cover that can be locked.

Copyright© WC3 2025

166


Some Inverters Have Both a DC and an AC disconnect Provided



Copyright© WC3 2025

167

Fuses at DC Combiners



Verify that all fuses at a DC combiner are listed for PV use (see NEC 690.9(B)) and are rated for the maximum voltage of the system (NEC 110.3(B))

Copyright© WC3 2025

168

Equipment at the array




Equipment must be protected from damage. *NEC 110.27(B)*

Copyright© WC3 2025

169

Careful
consideration
should be given to
wire bending
space!



Copyright© WC3 2025

170

Large-Scale Solar PV Systems



Copyright© WC3 2025

171

Large Solar PV Systems

- ❑ Systems that are at least 5,000kw (5MW), and are not under exclusive control of the utility, are permitted to comply with *NEC* Article 691.
 - Article 691 offers a lot of flexibility to engineered designed systems.
 - Article 691 supersedes Article 690 if conflicting requirements apply.
- ❑ Smaller systems (smaller than 5MW) are required to comply with Article 690.

Copyright© WC3 2025


172




173



174



175



176


Wire Support System



Copyright© WC3 2025

177

Wire Harness System



Many modern large-scale solar PV systems utilize listed wire harness systems for combining dc strings together.

Copyright© WC3 2025

178

Wire harness system.



Copyright© WC3 2025


179

Wire harness system.



Copyright© WC3 2025

180



181




182



183



184



Medium Voltage (MV) Connections

Copyright© WC3 2025

185



Some inverter skids are mounted to driven piles.

Copyright© WC3 2025


186



YES! Privately owned substations (ie. NOT owned by a utility) are required to comply with the NEC as well as other typical standards such as NESC (C2).

Copyright© WC3 2025

187



Solar tracking systems must be listed per UL 3703. The racking systems themselves must be listed per UL 2703.

Copyright© WC3 2025

188

Ground-Mounted System Racking With Integrated Bonding



Copyright© WC3 2025

189

Signage



190

Signage, Per NEC 110.21(B)




Copyright© WC3 2025

- ❑ Signs must be durable and be able to handle the environment they are installed in.
- ❑ Signage cannot be hand-written.
- ❑ The markings must adequately warn of the hazard using effective words and/or symbols.

191

Signage at Service Equipment

A sign is required at the service equipment to include the words "CAUTION: MULTIPLE SOURCES OF POWER." NEC 705.10.



The sign must also note the location of all power production disconnecting means for the premises. NEC 705.10.

Copyright© WC3 2025


192

Rapid Shutdown Signage

Rapid shutdown sign required per *NEC* 690.12(D) [previously 690.56(C)].

SOLAR PV SYSTEM EQUIPPED WITH RAPID SHUTDOWN

TURN RAPID SHUTDOWN SWITCH TO THE "OFF" POSITION TO SHUTDOWN PV SYSTEM AND REDUCE SHOCK HAZARD IN ARRAY



Copyright© WC3 2025

193

Rapid Shutdown Signage


690.12(D)(1) [previously 690.56(C)(1)] Buildings with More Than One Rapid Shutdown Type:

- ❑ For buildings that have PV systems with **both** rapid shutdown types **or** a PV system with a rapid shutdown type and a PV system with no rapid shutdown, a detailed plan view diagram of the roof shall be provided showing each different PV system and a dotted line around areas that remain energized after the rapid shutdown switch is operated.

194

Rapid Shutdown Signage For Buildings with More Than One Rapid Shutdown Type

Example of a plaque showing which portion(s) of the PV system are equipped with rapid shutdown and which are not:



Copyright© WC3 2025

195

Rapid Shutdown Signage

- ❑ **690.12(D)(2) [previously 690.56(C)(2)] Rapid Shutdown Switch.** A rapid shutdown switch shall have a label located on or no more than (3 ft) from the switch that includes the following wording: **“RAPID SHUTDOWN SWITCH FOR SOLAR PV SYSTEM”**
- ❑ The label shall have all letters capitalized and having a minimum height of 9.5 mm (3/8 in.), in white on red background.


Rapid Shutdown Switch For Solar PV System

Sign located next to the rapid shutdown disconnect

Copyright© WC3 2025


196

Sign at Point of Interconnection




197

Signage at PV Backfed Breakers




198

Sign at String Inverters



199

Wiring Methods



200

External Identification Of DC Wiring



Copyright© WC3 2025

201

Warning Signage

NEC 690.13(B):

- ❑ A sign is required at any disconnect or electrical box where both sides of terminals can be energized in the open position and must state:

**WARNING ELECTRIC SHOCK HAZARD
TERMINALS ON THE LINE AND LOAD SIDES
MAY BE ENERGIZED IN THE OPEN POSITION.**

Copyright© WC3 2025

202

AC disconnects



Copyright© WC3 2025


Here is an example of an AC disconnect switch (used for a PV system) that would require the following sign:

**WARNING ELECTRIC SHOCK HAZARD
TERMINALS ON THE LINE AND LOAD
SIDES MAY BE ENERGIZED IN THE
OPEN POSITION.**

NOTE: It's STRONGLY recommended that only AC disconnects with dead-fronts be used for a PV system or provide a lock for the disconnect (if the disconnect is readily accessible to unqualified persons)!


203

This disconnect includes dead-fronts to protect line terminals.



Copyright© WC3 2025

204



205